

**Exceptional Value Carpet Tile** 

The EuroTile™ series is our most affordable modular carpet collection



Express Tile Ships in 24 hours.



Stain Proof - No Exceptions™

This carpet is stain proof - ideal for environments with frequent spills including corridors, rental units and hospitality spaces.



## 10 Year Warranties

- Commercial wear
- Commercial backing performance
   Stain Proof − No Exceptions<sup>™</sup>
   See full text for details.

Style 7071

02 Agate 01 Travertine 03 Lead 05 Taupe 06 Ebony 07 Navy



Style Supplier	7071 rubicon@wor <u>k</u> tile Kraus®	
CONSTRUCTION		
Fiber system Construction Backing system Pile weight Pile height Gauge Stitches Density	100% BCF Polypropylen Multi-level scroll loop EuroBac™ Modular 18 oz./y² 0.13″ 1/12 10.2 s.p.i. 6400	610 g/m 3.5 mm 47.2 rows/10 cm 40.0 stitches/10 cm
PERFORMANCE		
Static generation Flammability	3.0 kV or less (AATCC 134) Radiant Panel ASTM E648 – Class I (direct glue) Methenamine Pill – DOC FF 1-70 - passes	
Colorfastness to light	5.0 (AATCC 16)	
INSTALLATION		
Modular size (w x l) Packaging	19.7" x 19.7" 20 tiles/carton 54 lbs/carton 32 cartons/pallet	50 cm x 50 cm 6 y²/carton
Recommended adhesive Installation method	AAT 320 Premium Adhesive™ Quarter-Turn	
WARRANTIES		
10 Year Warranties (see full text for details)	Commercial wear Commercial backing performance Stain Proof – No Exceptions™	

The natural characteristics of geometric or linear patterns in carpet tile can result in double-dark or double-light lines at the seam and to some degree a pattern run-off or bias. This is not a manufacturing defect. These characteristics should always be taken into consideration when choosing the installation method of a modular carpet. While select styles are offered in both modular and broadloom formats, they are not an exact match since the equipment used in the manufacturing of both patterns are entirely different. @work is a registered trademark of Kraus® \*Percentages of recycled content are accurate at date of printing. The availability of these inputs may fluctuate. Refer to krausflooring.com for the most current specifications.

E&OE.

